## **EAST Search History**

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S26 0	238	377/78.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/12/18 15:13
S26 1	6	377/78.ccls. and phase and ccd	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/12/18 15:17
S26 2	218	257/246.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/12/18 15:18
S26 3	0	257/246.ccls. and ccr and register	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/12/18 15:18
S26 4	61	257/246.ccls. and ccd and register	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON .	2007/12/18 15:18
S26 5	28	257/246.ccls. and ccd and register and (phase or clock) with three	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/12/18 15:19
S26 6	10	257/246.ccls. and ccd and register and (phase or clock) with three and resolution	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/12/18 15:26
S26 7	1225	ccd and register and (phase or clock) with three and resolution	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/12/18 15:27
526 8	. 746	ccd and register and (phase or clock) with three and resolution with (low or high)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/12/18 15:27

## **EAST Search History**

S26 9	486	ccd and register with shift and (phase or clock) with three and resolution with (low or high)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/12/18 15:28
S27 0	99	ccd and register with shift with second and (phase or clock) with three and resolution with (low or high)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/12/18 15:28
S27 1	64	ccd and register near4 shift near4 second and (phase or clock) with three and resolution with (low or high)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/12/18 15:37
S27 2	′33	ccd and register near4 shift near4 second and (phase or clock) with three and resolution same (low same high)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/12/18 15:37



Home | Login | Logout | Access Information | Alerts | Purchase History |

## Welcome United States Patent and Trademark Office

Search Results

**BROWSE** 

SEARCH

**IEEE XPLORE GUIDE** 

Results for "(((shift <near> register)<in>metadata)<and>((high <near> low <near> re..."

Your search matched 15 of 2214 documents.

A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order.

**Modify Search** 



» Search Options

View Session History

**New Search** 

» Key

IEEE JNL

IEEE Journal or Magazine

**IET JNL** 

IET Journal or Magazine

**IEEE CNF** 

IEEE Conference

Proceeding

**IET CNF** 

IET Conference

Proceeding

IEEE STD IEEE Standard

(((shift <near> register)<in>metadata)<and>((high <near> low <near> resolution)<in></in></near></near></and></in></near>						
☐ Check to search only within this results set						
Display	Format: 📵 Citat	tion C Citation &	Abstract			
IE	EEE/IET	Books	Educational Cou	rses A		
IEEE/IET	「journals, transact	ions, letters, maga	zines, conference proceed	ings, and		
← view se	elected items	Select All Deselec	t All			
<u>⊓</u> 1.	A complete 18-bit audio D/A converter Baginski, P.; Brokaw, P.; Wurcer, S.; Solid-State Circuits Conference, 1990. Digest of Technical Papers. 37th ISSC 14-16 Feb. 1990 Page(s):202 - 203, 296 Digital Object Identifier 10.1109/ISSCC.1990.110195  AbstractPlus   Full Text: PDF(200 KB) IEEE CNF Rights and Permissions					
<u> </u>	Kaufman, H.J.; Sid Consumer Electror Volume 36, Issue Digital Object Iden	nics, IEEE Transactions. 2, May 1990 Page(statifier 10.1109/30.542 Text: <u>PDF(</u> 364 KB)	ons on s):137 - 141 80			
<u> </u>	Kaufman, H.J.; Sid Circuits and Syster 1-3 May 1990 Page Digital Object Ident	-Ahmed, M.A.; ms, 1990., IEEE Inte e(s):3023 - 3026 vol. tifier 10.1109/ISCAS Text: <u>PDF</u> (464 KB)	.1990.112648	r scannec		
☐ 4.			erline-transfer CCD image (.; Kosaza, H.; Sakamoto, S.			

Awane, K.;

Rights and Permissions

Chia-Nan Yeh; Yen-Tai Lai;

Electron Devices, IEEE Transactions on

Volume 33, Issue 4, Apr 1986 Page(s):458 - 463 AbstractPlus | Full Text: PDF(904 KB) | IEEE JNL

5. Low power readout control circuit for high resolution CMOS image sens